



HIGHLIGHT PRODUCTS

2024.H1

DESIGNED & ENGINEERED IN GERMANY

cameolight.com

LOCATION:

TANTE MIA TANZT
VECHTA (GERMANY)

PRODUCTS USED:

OTOS® H5 (51 UNITS)
OPUS® H5 (24 UNITS)
ZENIT® W600 SMD (18 UNITS)



Cameo® is a registered brand of the Adam Hall Group.



SOUND
TECHNOLOGY

LIGHT
TECHNOLOGY

STAGE
EQUIPMENT

HARDWARE
FOR FLIGHTCASES

ADAM HALL GROUP BRANDS



OUR MISSION

Cameo® – For Lumen Beings

TO CONNECT AND EMPOWER ALL LUMEN BEINGS AROUND THE WORLD.



facebook.com/@Cameo



youtube.com/@CameoOfficial



BLOG blog.adamhall.com



linkedin.com/Cameo Light



instagram.com/cameo_light



Cameo® is a registered brand of the Adam Hall Group.

**COMPACT DESIGN.
DO EPIC.**





HIGHLIGHT

cameo

AZOR® SP2

COMPACT SPOT PROFILE MOVING HEAD

- ▶ 300 W LED with 13,000 lm luminous flux
- ▶ Motorized framing blades on 4 layers (+/- 60° rotable)
- ▶ Zoom range: 5° - 50°
- ▶ CMY colour mixing and additional colour wheel with 8 dichroic colour filters
- ▶ Rotating gobo wheel with 8 indexable/rotatable, exchangeable glass gobos + open
- ▶ Overlapping prisms (linear + circular)
- ▶ Linear CTO for colour temperature modulation in lighting setups
- ▶ Selectable PWM frequencies up to 25 kHz for flicker-free operation
- ▶ Silent operation in 3 different fan modes



FOR MORE INFORMATION
PLEASE SCAN THE QR-CODE

AZOR® SP2





HIGHLIGHT



AZOR® W2

COMPACT WASH MOVING HEAD

- ▶ 7 x 40 W RGBL LEDs with 3,600 lm luminous flux
- ▶ Zoom range: 4° - 50°
- ▶ Single pixel control of all 7 LEDs
- ▶ Eclipse Burst Effect for blinder, strobe and pixel effects
- ▶ Selectable PWM frequencies up to 25 kHz for flicker-free operation
- ▶ iDMX stick input for wireless DMX connection
- ▶ OLED display with 4 buttons



FOR MORE INFORMATION
PLEASE SCAN THE QR-CODE

AZOR® W2





HIGHLIGHT



OTOS® WASH SERIES

IP65 WASH MOVING HEAD

- ▶ RGBL LEDs with 7 x 40W, 16 x 40W or 31 x 40W
- ▶ Controllable FX LED ring
- ▶ Multi-zoom technology: single-zoom (W3), dual-zoom (W6) or multi-zoom (W12)
- ▶ Zoom lens and zoom range: 4° - 60°
- ▶ Control options via integrated W-DMX™ transceiver, DMX & RDM

FOR MORE INFORMATION
PLEASE SCAN THE QR-CODE

OTOS® SERIES



redefine
your
connections






HIGHLIGHT



PIXBAR® 400 IP G2

IP65 RGBW LED BAR

- ▶ Simple and efficient interconnection of up to 3 units with the optional STACK-KIT
- ▶ Adjustable feet for truss-bracing positioning
- ▶ Optional VERTI-MOUNT for standing or hanging application
- ▶ Easy slide-in filter mechanism with locking mechanism
- ▶ Fanless cooling design
- ▶ High brightness and accurate colour mixing
- ▶ SPIN16® included



FOR MORE INFORMATION
PLEASE SCAN THE QR-CODE

PIXBAR® 400 IP G2



ACCESSORIES





HIGHLIGHT



PIXBAR® 600 IP G2

IP65 RGBWAUV LED BAR

- ▶ Simple and efficient interconnection of up to 3 units with the optional STACK-KIT
- ▶ Adjustable feet for truss-bracing positioning
- ▶ Optional VERTI-MOUNT for standing or hanging application
- ▶ Easy slide-in filter mechanism with locking mechanism
- ▶ Fanless cooling design
- ▶ High brightness and accurate colour mixing
- ▶ SPIN16® included



FOR MORE INFORMATION
PLEASE SCAN THE QR-CODE

PIXBAR® 600 IP G2



ACCESSORIES






HIGHLIGHT



PIXBAR® TW IP G2

IP65 TUNABLE WHITE LED BAR

- ▶ Simple and efficient interconnection of up to 3 units with the optional STACK-KIT mechanism
- ▶ Adjustable feet for truss-bracing positioning
- ▶ Optional VERTI MOUNT for standing or hanging application
- ▶ Easy slide-in filter mechanism with locking mechanism
- ▶ Fanless cooling design
- ▶ High brightness and accurate white mixing
- ▶ SPIN16® included



FOR MORE INFORMATION
PLEASE SCAN THE QR-CODE

PIXBAR® TW IP G2



ACCESSORIES





HIGHLIGHT



PIXBAR® SMD IP G2

IP65 SMD LED BAR

- ▶ Simple and efficient interconnection of up to 3 units with the optional STACK-KIT
- ▶ Adjustable feet for truss-bracing positioning
- ▶ Optional VERTI-MOUNT for standing or hanging application
- ▶ Easy slide-in filter mechanism with locking mechanism
- ▶ Fanless cooling design
- ▶ High brightness and accurate colour mixing
- ▶ 3 LED rows with 16 segments each individually controllable
- ▶ SPIN16® included



FOR MORE INFORMATION
PLEASE SCAN THE QR-CODE

PIXBAR® SMD IP G2



ACCESSORIES





LOCATION:
PHANTASIALAND
BRÜHL (GERMANY)

PRODUCTS USED:
OPUS® X PROFILE (12 UNITS)
OPUS® S5 (35 UNITS)
OPUS® SP5 (8 UNITS)
OPUS® W5 (22 UNITS)
EVOS® W7 (28 UNITS)



HIGHLIGHT

cameo

ZENIT® W300 SMD

OUTDOOR SMD LED WASH LIGHT

- ▶ Featuring a total of 270 SMD 4-in-1 LEDs with up to 19,000 lm luminous flux for extreme brightness
- ▶ Precise and high-resolution colours, as well as mixed colours in the RGBW spectrum
- ▶ 6 individually controllable segments
- ▶ Boost in blinder mode for temporarily increased output
- ▶ IP65 rated for permanent outdoor use
- ▶ High-resolution dimmer response thanks to 16-bit technology
- ▶ 2,700 - 6,500 K colour temperature and CRI >85 for uncompromised colour reproduction
- ▶ Integrated 2.4 GHz W-DMX™ transceiver
- ▶ Control via W-DMX™, DMX and RDM (via DMX and W-DMX™)
- ▶ Temperature-controlled fans for optimised low-noise operation



FOR MORE INFORMATION
PLEASE SCAN THE QR-CODE

ZENIT® W300 SMD



ACCESSORIES





HIGHLIGHT

cameo

ZENIT® W300 TW

OUTDOOR LED WASH LIGHT TUNABLE WHITE VERSION

- ▶ 21 x 12 W Tunable White LEDs with 23,000 lm total output for intensive white mixing
- ▶ 18° beam and 35° field angles without diffuser
- ▶ Optional SnapMag® filter frames for 25°, 45° or 100° and elliptical 60° x 10° beam angle selection and installation without tools or dismantling
- ▶ Built-in 2.4 GHz W-DMX™ transceiver
- ▶ Wireless master and slave operation
- ▶ W-DMX™, RDM, DMX or IR control additionally standalone modes with automated programs
- ▶ IP65 rating for outdoor use
- ▶ Low-noise temperature controlled fans for optimized operation
- ▶ Colour temperature from 2,600 K - 6,500 K




FOR MORE INFORMATION
PLEASE SCAN THE QR-CODE

PIXBAR G2



ACCESSORIES






HIGHLIGHT



F2 FC+

HIGH-POWER FRESNEL WITH RGBW LED

- ▶ Full colour fresnel with special RGBAL LED type is matching to P2 FC
- ▶ Brilliant colours and precise white balance
- ▶ High CRI (>94) and TLCI (>93) for natural colour reproduction
- ▶ Adjustable colour temperature from 1,800 to 8,000 K
- ▶ Continuous zoom for beam angles from 18° - 55°



FOR MORE INFORMATION
PLEASE SCAN THE QR-CODE

F2 FC+



ACCESSORIES




COMING SOON

ORON® H2

IP65 HYBRID MOVING HEAD
WITH LASER ENGINE

- ▶ 260W Laser Phosphor Engine
- ▶ Zoom range: 0,8°-35°
- ▶ 19 fixed gobos + open and 12 rotating gobos + open
- ▶ 2 prism layers with 8 effects (prism, multicolor + frost)
- ▶ Shock protective touring case insert included
- ▶ Only 33 kg




COMING SOON

OPUS® X4

1400W LED SPOT-PROFILE
MOVING HEAD

- ▶ 55,000 lm total output
- ▶ Framing blades with +- 60° rotation
- ▶ Zoom range: 5° - 55°
- ▶ Linear CMY, CTO
- ▶ 2x gobo wheels, 2x colour wheels & an animation wheel




COMING SOON

DURA® LINE

IP67 INSTALL SPOT
WITH RGBW LED

- ▶ 14x 4W / 28x 4W calibrated RGBW LEDs
- ▶ High efficiency – 40lm/W + Convection cooling
- ▶ Original Amphenol LTW connectors
- ▶ UNICON® compatible
- ▶ IP67, IK08 and C5-M coating
- ▶ 12° beam angle (optional filters 20°, 40°, 60°, 60°x10°)
- ▶ Super light-weight 2,7 kg (DL50) / 5,6 kg (DL100)



LOCATION:
WESTMINSTER PALACE
LONDON (UNITED KINGDOM)

PRODUCTS USED:
ZENIT® W600



LOCATION:

NATURE ONE
KASTELLAUN (GERMANY)

PRODUCTS USED:

OTOS® H5 (156 UNITS)
OTOS® B5 (18 UNITS)
AZOR® B1 (120 UNITS)
AZOR® S2 (60 UNITS)
ZENIT® W600 (30 UNITS)
TENIT® SMD (20 UNITS)
TRIBAR 400 IR TRI LED (60 UNITS)



for lumen beings

**DISCOVER OUR
NEW CATALOGUE
ONLINE NOW!**

CATALOGUE





cameolight.com

For more information please visit:
cameolight.com



facebook.com/@Cameo



youtube.com/@CameoOfficial



blog.adamhall.com



linkedin.com/Cameo Light



instagram.com/cameo_light

The information contained in this publication, including numerical data, has been prepared as a general guide to the products, but intending buyers and users must satisfy themselves as to the suitability and the safety of the products for their particular purposes and duties. No responsibility is assumed for any errors herein. The company reserves the right to alter the designs and material specifications of products shown in this publication without notice.

Cameo® is a
registered brand of



adam hall experience
event technology

SOUND
TECHNOLOGY

LIGHT
TECHNOLOGY

STAGE
EQUIPMENT

HARDWARE
FOR FLIGHTCASES

share the experience at
adamhall.com