




STINGER® G3 SERIES
MULTIFUNCTIONAL PA SPEAKERS & SUBWOOFERS



workhorse noun [C] UK /'wə:khɔ:s/

"A dependable performer; a steady, responsible worker who assumes a heavy workload."





STINGER® G3 SERIES MULTIFUNCTIONAL PA SPEAKERS & SUBWOOFERS

High-performance workhorse loudspeakers for outstanding sound reinforcement - that was our goal creating the STINGER G3 series. We've combined optimized components and smart details in active and passive models to ensure exceptional reliability and ease of use. STINGER multipurpose systems and subwoofers are your go-to choice for affordable pro audio quality. It's time you saddled up!



RE-DEFINING MULTITALENT

Application presets enable instant frequency response contouring.



INPUT VARIETY

Dual line and mic level inputs add application versatility to active STINGER G3 models.



DYNX® DSP-TECHNOLOGY

Including multiband limiter and crossover functions, LD Systems' DynX DSP technology ensures perfect time alignment and distortion-free performance even at maximum levels.



TAKE AIM

LD Systems' Dual-Tilt pole mount allows 0° and 5° orientation angles.



ENGINEERED FOR PERFECTION

Designed with BEM modeling of sound radiation and propagation, the HF waveguide reduces floor and ceiling reflections, effectively eliminates side lobes and achieves a controlled uniform coverage pattern.



Ultra tough impact resistant polyurea coating provides unrivaled durability.



ALL MODELS EQUIPPED WITH POWERCON COMPATIBLE CONNECTORS



4 x HEAVY-DUTY HANDLES

2 x M20 SPEAKER POLE INSERTS



Ultra tough impact resistant polyurea coating provides unrivaled durability.







INSTANT CARDIOID SUB ARRAY CONFIGURATION

2 X INTEGRATED KEEPER PLATES FOR STINGER CASTOR BOARD ATTACHMENT



SYSTEM INTEGRATION MADE EASY

PASSIVE





TECHNICAL SPECIFICATIONS

SPECIFICATIONS SPEAKERS:

Art. No.:	LDEB82G3	LDEB282G3	LDEB102G3	LDEB122G3	LDEB152G3	LDEB82AG3	LDEB282AG3	LDEB102AG3	LDEB122AG3	LDEB152AG3
Product type:	PA loudspeaker	PA loudspeaker	PA loudspeaker	PA loudspeaker	PA loudspeaker	PA loudspeaker	PA loudspeaker	PA loudspeaker	PA loudspeaker	PA loudspeaker
Type:	passive	passive	passive	passive	passive	active	active	active	active	active
Low/mid driver dimensions:		2 x 8"					2 x 8"			
HF driver dimensions:										
HF driver brand:	BMS	BMS	BMS	BMS	BMS	BMS	BMS	BMS	BMS	BMS
Dispersion (H x V):	90°x50°	90°x50°	90 ° x 50 °	90°x50°	90°x50°	90°x50°	90°x50°	90°x50°	90°x50°	90°x50°
Load rating (RMS):	250 W	400 W	300 W	400 W	500 W	300 W	500 W	300 W	500 W	
Peak power:	500W	800W	600 W	800 W	1000W	600 W	1000 W	600 W	1000 W	1000 W
Frequency response:										50 - 20000 Hz
SPL (1W/1m):										
Max. SPL (peak):										133 dB
Impedance:										
Loudspeaker inputs:										
Loudspeaker inputs: Inputs:	1 Speakon compatible	1 Speakon compatible	1 Speakon compatible	1 Speakon compatible	1 Speakon compatible	2 x Line/Mic In on XLR, 6.3 mm Jack / 1 x Line Out on XLR	2 x Line/Mic In on XLR, 6.3 mm Jack / 1 x Line Out on XLR	2 x Line/Mic In on XLR, 63 mm Jack / 1 x Line Out on XLR	2 x Line/Mic In on XLR, 6.3 mm Jack / 1 x Line Out on XLR	2 x Line/Mic In on XLR, 6.3 mm Jack / 1 x Line Out on XLR
						on XLR, 6.3 mm Jack / 1 x Line	on XLR, 6.3 mm Jack / 1 x Line	2 x Line/Mic In on XLR, 6.3 mm Jack / 1 x Line Out	on XLR, 6.3 mm Jack / 1 x Line Out	on XLR, 6.3 mm Jack / 1 x Line Out
	compatible	compatible	compatible	compatible	compatible	on XLR, 6.3 mm Jack / 1 x Line Out on XLR	on XLR, 6.3 mm Jack / 1 x Line Out on XLR	2 x Line/Mic In on XLR, 63 mm Jack / 1 x Line Out on XLR	on XLR, 6.3 mm Jack / 1x Line Out on XLR	on XLR, 6.3 mm Jack / 1 x Line Out on XLR
Inputs: Cabinet material:	compatible 12 mm Plywood	compatible 12 mm Plywood	compatible 12 mm Plywood	compatible 15 mm Plywood	compatible 15 mm Plywood	on XLR, 6.3 mm Jack / 1 x Line Out on XLR 12 mm Plywood	on XLR, 6.3 mm Jack / 1 x Line Out on XLR 12 mm Plywood	2 x Line/Mic In on XLR, 6.3 mm Jack / 1 x Line Out on XLR 12 mm Plywood	on XLR, 6.3 mm Jack / 1 x Line Out on XLR 15 mm Plywood	on XLR, 6.3 mm Jack / 1 x Line Out on XLR 15 mm Plywood
Inputs: Cabinet material: Cabinet surface:	compatible 12 mm Plywood Polyurea	compatible 12 mm Plywood Polyurea	compatible 12 mm Plywood Polyurea	compatible 15 mm Plywood Polyurea	compatible 15 mm Plywood Polyurea	on XLR, 6.3 mm Jack / 1 x Line Out on XLR 12 mm Plywood Polyurea	on XLR, 6.3 mm Jack / 1 x Line Out on XLR 12 mm Plywood Polyurea	2 x Line/Mic In on XLR, 63 mm Jack / 1 x Line Out on XLR 12 mm Plywood Polyurea	on XLR, 6.3 mm Jack / 1x Line Out on XLR 15 mm Plywood Polyurea	on XLR, 6.3 mm Jack / 1 x Line Out on XLR 15 mm Plywood Polyurea
Inputs: Cabinet material: Cabinet surface: Width:	compatible 12 mm Plywood Polyurea 270 mm	compatible 12 mm Plywood Polyurea 270 mm	compatible 12 mm Plywood Polyurea 325 mm	compatible 15 mm Plywood Polyurea 390 mm	compatible 15 mm Plywood Polyurea 480 mm	on XLR, 6.3 mm Jack / 1 x Line Out on XLR 12 mm Plywood Polyurea 270 mm	on XLR, 63 mm Jack / 1x Line Out on XLR 12 mm Plywood Polyurea 270 mm	2 x Line/Mic In on XLR, 63 mm Jack / 1 x Line Out on XLR 12 mm Plywood Polyurea 325 mm	on XLR, 6.3 mm Jack / 1 x Line Out on XLR 15 mm Plywood Polyurea 390 mm	on XLR, 6.3 mm Jack / 1 x Line Out on XLR 15 mm Plywood Polyurea 480 mm

SPECIFICATIONS SUBWOOFERS:

Art. No.:	LDESUB15G3	LDESUB18G3	LDESUB15AG3	LDESUB18AG3
Product type:	PA subwoofer	PA subwoofer	PA subwoofer	PA subwoofer
Туре:	passive	passive	active	active
Low/mid driver dimensions:				
Load rating (RMS):	600 W	800 W	450 W	800 W
Peak power:	1200 W	1600 W	900 W	1600W
Max. SPL (peak):				135 dB
			Main Level, Mode	Main Level, Mode
Inputs:				
Input connectors:			6.3 mm Jack, XLR	6.3 mm Jack, XLR
Cabinet material:	18 mm Plywood	18 mm Plywood	18 mm Plywood	18 mm Plywood
Cabinet surface:				
Width:	576 mm	677 mm	576 mm	677 mm
Height:	477 mm	547 mm		547 mm
Depth:	624 mm	740 mm	624 mm	740 mm
Weight:	29,7 kg	40.6 kg	31.9 kg	42.6 kg





STINGER SETS

Available in a variety of subwoofer and satellite configurations, STINGER sets are the perfect loudspeaker packages for music and speech. From rehearsal rooms and small-scale gigs to gala events and demanding outdoor sound reinforcement requiring extra low end there is a STINGER speaker set for you. Providing dynamic music reproduction with punch and clarity as well as excellent speech intelligibility, these loudspeaker packages come in powered and passive versions including all the necessary cables, speaker poles, protective covers and castor boards for easy subwoofer transport. Whether you are playing a club gig, performing at a private function or street festival, STINGER sets have got you and your audience covered.



Providing easy portability, this compact set is terrific for small gigs and functions that require excellent music and speech reinforcement.

Applications:

DJs | solo entertainers | singer-songwriters | private functions

Audience Size*:

150 music | 200 speech

PASSIVE SET

LDEBSETLOUNGE

Including:

- 2 x STINGER 8 G3
- 1 x STINGER SUB 15 G3
- •1x POWER AMP RACK DSP 45 K
- 2 x STINGER 8 G3 PC
- 1 x STINGER SUB 15 G3 PC

Recommended accessories:

- 2 x GRAVITY SSP WB SET 1 (GSSPWBSET1)
- · 3 x ADAM HALL CABLES K 4 S 425 SS 1000 (K4S425SS1000)

ACTIVE SET

I DEBSETI OUNGEA

Including:

- 2 x STINGER 8 A G3
- 1 x STINGER SUB 15 A G3
- 2 x STINGER 8 G3 PC
- 1 x STINGER SUB 15 G3 PC
- 1 x STINGER SUB 15 G3 CB

- 2 x GRAVITY SSP WB SET 1 (GSSPWBSET1)
- · 2 x ADAM HALL CABLES K4 MMF 1000 (K4MMF1000)

^{*}NOTE: Audience size specifications are approximate only. The actual numbers may vary depending on room acoustics and environment.







This set is the perfect all-round package for small to medium-sized gigs and functions providing a tight and punchy low end from the two subwoofers.

Applications:

small bands | DJs | private functions

Audience Size*:

200 music | 300 speech

PASSIVE SET

I DFBSFTFVFN1

Including:

- 2 x STINGER 10 G3
- 2 x STINGER SUB 15 G3
- •1x POWER AMP RACK DSP 45 K
- 2 x STINGER 10 G3 PC
- 2 x STINGER 10 G3 CB
- 2 x STINGER SUB 15 G3 PC
- 2 x STINGER SUB 15 G3 CB

Recommended accessories:

- 2 x GRAVITY SP 2342 B (GSP2342B)
- · 2 x ADAM HALL CABLES K 4 S 425 SS 1000 (K4S425SS1000)
- · 2 x ADAM HALL CABLES K 4 S 225 SS 0200 (K4S215SS0200)

ACTIVE SET

I DEBSETEVENTA

Including:

- 2 x STINGER 10 A G3
- 2 x STINGER SUB 15 A G3
- 2 x STINGER 10 G3 PC
- · 2 x STINGER 10 G3 CB
- 2 x STINGER SUB 15 G3 PC
- 2 x STINGER SUB 15 G3 CB

- 2 x GRAVITY SP 2342 B (GSP2342B)
- 4 x ADAM HALL CABLES 8101 PSDT 0300 (8101PSDT0300)

^{*}NOTE: Audience size specifications are approximate only. The actual numbers may vary depending on room acoustics and environment.







Excellent for live clubs and touring bands, this set is a superb choice wherever highly dynamic music reinforcement with plenty of power and punch is of prime importance.

Applications:

bands | live clubs | large private functions | corporate events | AV presentations

Audience Size*:

250 music | 350 speech

PASSIVE SET

LDEBSETPOWER

Including:

- 2 x STINGER 15 G3
- 2 x STINGER SUB 18 G3
- •1x POWER AMP RACK DSP 45 K
- 2 x STINGER 15 G3 PC
- 2 x STINGER 15 G3 CB
- 2 x STINGER SUB 18 G3 PC
- 2 x STINGER SUB 18 G3 CB

Recommended accessories:

- 2 x GRAVITY SP 2342 B (GSP2342B)
- · 2 x ADAM HALL CABLES K 4 S 425 SS 1000 (K4S425SS1000)
- · 2 x ADAM HALL CABLES K 4 S 225 SS 0200 (K4S215SS0200)

ACTIVE SET

I DEBSETPOWERA

Including:

- 2 x STINGER 15 A G3
- 2 x STINGER SUB 18 A G3
- 2 x STINGER 15 G3 PC
- 2 x STINGER 15 G3 CB
- 2 x STINGER SUB 18 G3 PC
- 2 x STINGER SUB 18 G3 CB

- 2 x GRAVITY SP 2342 B (GSP2342B)
- 4 x ADAM HALL CABLES 8101 PSDT 0300 (8101PSDT0300)

^{*}NOTE: Audience size specifications are approximate only. The actual numbers may vary depending on room acoustics and environment.







Sets include slip covers and castor boards.



Delivering a massive low-end with punch and clarity, this set is ideal for outdoor sound reinforcement. With a quartet of subwoofers an two 15" tops, it easily covers medium-sized gigs at town fairs, street festivals and in marquees.

Applications:

outdoor sound reinforcement for bands | DJs | large private functions

Audience Size*:

300 music | 400 speech

PASSIVE SET

I DEDCETIMBACT

Including:

- 2 x STINGER 15 G3
- 4 x STINGER SUB 18 G3
- •1x POWER AMP RACK DSP 45 K
- 2 x STINGER 15 G3 PC
- 2 x STINGER 15 G3 CB
- 4 x STINGER SUB 18 G3 PC
- 4 x STINGER SUB 18 G3 CB

Recommended accessories:

- 2 x GRAVITY SP 2342 B (GSP2342B)
- · 2 x ADAM HALL CABLES K 4 S 425 SS 1000 (K4S425SS1000)
- · 2 x ADAM HALL CABLES K 4 S 225 SS 0200 (K4S215SS0200)

ACTIVE SET

I DERSETIMPACTA

Including:

- 2 x STINGER 15 A G3
- 4 x STINGER SUB 18 A G3
- 2 x STINGER 15 G3 PC
- 2 x STINGER 15 G3 CB
- 4 x STINGER SUB 18 G3 PC
- 4 x STINGER SUB 18 G3 CB

- 2 x GRAVITY SP 2342 B (GSP2342B)
- 4 x ADAM HALL CABLES 8101 PSDT 0150 (8101PSDT0150)

^{*}NOTE: Audience size specifications are approximate only. The actual numbers may vary depending on room acoustics and environment.









Including a pair of slim, low-profile satellites and two subwoofers, this set is a great option for events that require excellent speech intelligibility and extended coverage.

Applications:

gala events | corporate conferences | large private functions

Audience Size*:

250 music | 350 speech

PASSIVE SET

LDEBSETGALA

Set consisting of:

- 2 x STINGER 28 G3
- 2 x STINGER SUB 18 G3
- •1x POWER AMP RACK DSP 45 K
- 2 x STINGER 28 G3 PC
- 2 x STINGER 28 G3 CB
- 2 x STINGER SUB 18 G3 PC
- 2 x STINGER SUB 18 G3 CB

Recommended accessories:

- 2 x GRAVITY SP 2342 B (GSP2342B)
- · 2 x ADAM HALL CABLES K 4 S 425 SS 1000 (K4S425SS1000)
- · 2 x ADAM HALL CABLES K 4 S 225 SS 0200 (K4S215SS0200)

ACTIVE SET

LDEBSETGALAA

Set consisting of:

- 2 x STINGER 28 A G3
- 2 x STINGER SUB 18 A G3
- · 2 x Stinger 28 G3 PC
- · 2 x Stinger 28 G3 CB
- 2 x Stinger Sub 18 G3 PC
- 2 x STINGER SUB 18 G3 CB

- 2 x GRAVITY SP 2342 B (GSP2342B)
- 2 x ADAM HALL CABLES 8101 PSDT 0300 (8101PSDT0300)

^{*}NOTE: Audience size specifications are approximate only. The actual numbers may vary depending on room acoustics and environment.







Sets include slip covers and castor boards.

welcome to the digital age.

DSP SERIES

PROFESSIONAL DSP POWER AMPLIFIERS

The LD Systems® DSP power amps are professional 4-channel power amplifier with extensive DSP control. Designed for demanding large-scale sound reinforcement and concert-quality performance, they deliver a massive 1,200 watts per channel and 2 x 2,400 watts bridged. The high-efficiency Class H topology and switch mode power supply with power factor correction (PFC) provide a wide dynamic range and excellent transient response.

These amps feature comprehensive protection circuitry including power-up, DC, overcurrent, thermal and short circuit protection plus current and clip limiters to prevent SMPS overload and loudspeaker damage. Together with a pair of temperature controlled fans, they ensure exceptional reliability in the most demanding applications. The 24-bit DSP allows precise control with FIR and IIR filters, parametric EQ, crossover, delay, RMS and peak limiter functions. User configurable loudspeaker presets with password protection enable fast setup.

For optimal speaker performance and safe operation the DSP power amps are equipped with an LD Systems® loudspeaker preset library, and the included software enables computer control and monitoring.









DSP 44 K RACKPROFESSIONAL DSP POWER AMPLIFIER
WITH DANTE™ INTERFACE

DSP 45 K RACKPROFESSIONAL DSP POWER AMPLIFIER

- . 4-channel power amplifier with DSP control / + Dante™ enabled (DSP 44 K)
- . 4 x 1,200 watts @ 4 and 2 ohms, 2 x 2,400 watts bridged @ 4 ohms
- . 10 Hz 22 kHz frequency response with 120 dB dynamic range
- . 24-bit/48kHz DSP with FIR and IIR filters, parametric EQ, crossover, delay, RMS and peak limiters
- DC, overcurrent, thermal and short circuit protection, soft start, clip and SMPS overload limiters
- . Dual temperature-controlled fans
- Power factor correction (PFC)
- . Menu driven 4-line display with rotary encoder and security lock
- . Includes control and monitoring software and LD Systems® Loudspeaker Preset Library

SPECIFICATIONS:

Art.No.:	LDDSP44KRACK	LDDSP45KRACK
Product type:	Power Amplifier	Power Amplifier
Type:	4-channel	4-channel
Rated ouput power (1kHz @ 2 0hms):	4 x 1200 W	4 x 1200 W
Rated ouput power (1kHz @ 4 0hms):	4 x 1200 W	4 x 1200 W
Rated ouput power (1kHz @ 8 0hms):	4 x 675 W	4 x 675 W
Rated ouput power (1kHz @ 4 0hms, bridged):	2 x 2400 W	2 x 2400 W
High Z 70 V rms / 100 V peak:	4 x 1200 W	4 x 1200 W
High Z 100 V rms / 140 V peak:	2 x 2400 W	2 x 2400 W
Output circuitry:	Class H	Class H
Frequency response:	10 Hz - 22 kHz	10 Hz - 22 kHz
THD:	< 0.05 % @ 1 kHz	< 0.05 % @ 1 kHz
Signal-to-noise ratio:	104 dB	104 dB
Protection circuits:	clip limiter , DC protection , Multiband limiter , over-current , RMS speaker limiter , short circuit , soft start , thermal protection	clip limiter , DC protection , Multiband limiter , over-current , RMS speaker limiter , short circuit , soft start , thermal protection
Controls:	Direct access buttons , Exit / lock button , On / off switch , Push encoder	Direct access buttons , Exit / lock button , On / off switch , Push encoder
Indicators:	LC display	LC display
Line inputs:	4	4
Line input connectors:	Neutrik XLR	Neutrik XLR
Line outputs:	4	4
Line output connectors:	Neutrik XLR	Neutrik XLR
Loudspeaker outputs:	4	4
Speaker output connections:	Speakon	Speakon
Cooling:	2 fans, temperature controlled	2 fans, temperature controlled
Maximum Ambient Temperature:	0 - 40°	0 - 40°
Operating voltage:	220 V AC - 240 V AC, 50-60 Hz , Switching Power Supply	220 V AC - 240 V AC, 50-60 Hz , Switching Power Supply
Relative Humidity:	< 80% (non-condensing)	< 80% (non-condensing)
Power consumption @ full load:	1900 W	1900 W
Dimensions (W x H x D):	482 mm x 89 mm x 320 mm	482 mm x 89 mm x 320 mm
Weight:	17.9 kg	17.9 kg
Features:	$19^{\rm w}$ / 2 U , Active Power Factor Correction , Computer control software, Dante interface , DSP controlled , Ethernet , LD Systems loudspeaker preset library , USB front port	19" / 2 U , Active Power Factor Correction , Computer control software, DSP controlled, Ethernet, LD Systems loudspeaker preset library , USB front port

Art. No.:	LDDSP44KPB/ LDDSP45KPB
Product type:	19" Patchbay
Type:	4-channel
Connectors:	2 x RJ45 (LDDSP45KPB only 1 x RJ45), 4 x Neutrik Speakon, 4 x Neutrik XLR Female, 2 x Neutrik XLR Male
Material / Surface:	Steel, powder coated
Dimensions (W x H x D):	19"/ 1 HE, 483 mm x 44,5 mm x 110 mm
Weight:	1.5 kg

WORKHORSE WALL AND TRUSS MOUNT ACCESSORIES



STINGER 8 G3 WMB

LDEB82G3WMB SWIVEL WALL MOUNT FOR STINGER 8"

STINGER 8 (A)G3 WMB 1

LDEB82G3WMB1 / LDEB82AG3WMB1 TILT AND SWIVEL WALL MOUNT FOR STINGER 8"

STINGER 28 G3 WMB

LDEB282G3WMB SWIVEL WALL MOUNT FOR STINGER 2 x 8"



STINGER 28 (A)G3 WMB 1

GSPWMBS30B / LDEB282AG3WMB1 TILT AND SWIVEL WALL MOUNT FOR STINGER 2 x 8" ACTIVE /PASSIVE

STINGER 10 G3 WMB

LDEB102G3WMB SWIVEL WALL AND CEILING MOUNT FOR STINGER 10"

STINGER 10 G3 WMB 1

LDEB102G3WMB1 TILT AND SWIVEL WALL MOUNT FOR STINGER 10"



STINGER G3 WMB

LDEBG3WMB SWIVEL WALL MOUNT FOR STINGER 12" AND STINGER 15"

STINGER G3 WMB 1

LDEBG3WMB1 TILT AND SWIVEL WALL MOUNT FOR STINGER 12" AND STINGER 15"

STINGER G3 SCP

LDEBG3SCP TRUSS MOUNT CLAMP SET FOR STINGER 8" AND STINGER 10"





NO TOOLS REQUIRED



3-POINT SUSPENSION



AUTOMATIC LOCKING



2-HAND SAFETY RELEASE



PAN & TILT



ADJUSTABLE WHILE MOUNTED

STINGER G3 TMB

LDEBG3TMB
TRUSS MOUNT BRACKET FOR STINGER 12" AND STINGER 15"

WORKHORSE TRANSPORT ACCESSORIES



STINGER 8 G3 PC LDEB82G3PC PROTECTIVE COVER FOR STINGER 8"



STINGER 28 G3 PC LDEB282G3PC PROTECTIVE COVER FOR STINGER 2 X 8"



STINGER 10 G3 PC LDEB102G3PC PROTECTIVE COVER FOR STINGER 10"



STINGER 12 G3 PC LDEB122G3PC PROTECTIVE COVER FOR STINGER 12"



STINGER 15 G3 PC
LDEB152G3PC
PROTECTIVE COVER FOR STINGER 15"



STINGER SUB 15 G3 PC
LDESUB15G3PC
PROTECTIVE COVER FOR STINGER SUB 15"



STINGER SUB 18 G3 PC LDESUB18G3PC PROTECTIVE COVER FOR STINGER SUB 18"



STINGER SUB 15 G3 CB
LDESUB15G3CB
CASTOR BOARD FOR STINGER SUB 15"



STINGER SUB 18 G3 CB LDESUB18G3CB CASTOR BOARD FOR STINGER SUB 18"



STINGER® G3 SERIES MULTIFUNCTIONAL PA SPEAKERS & SUBWOOFERS





DESIGNED & ENGINEERED IN GERMANY

MEET YOUR NEW EMPLOYEE OF THE YEAR:

Id-systems.com/STINGERG3